

FCI500

Cylinder Heated Ironer



FEATURES

- Finger protection and emergency button for more safety
- Durable Meta Aramid ironing belts for higher temperature resistance
- Automatic cool down
- 20 ironing programmes of which 6 are pre-set
- Indication of ironing speed and temperature
- Frequency controlled motor
- Easy to remove lint filters
- Standard anti-static bar
- Overheating check system (OCS) with 3 temperature sensors
- Ergonomic design
- Automatic display on the screen of the better area to place the linen.

OPTIONS

- Chrome-plated cylinder for a better thermal conduction and less maintenance
- Foot pedal with stop & reverse operation
- Front return
- Automatic led indicator that lights up the ironing table in 3 zones according to the temperature of the cylinder leading to a faster ironing process.

CONTROLS OPTIONS

- Evolis / Evolis Elite – fully programmable and customizable cycles 7" touch screen.
 - User-friendly screen with operating instructions built in as part of the control
 - Complete control content available in 34 languages



LARGE SURFACE CONTACT WITH LINEN

over an angle of 300° for high ironing capacity



AUTO ADJUSTABLE IRONING SPEED TECHNOLOGY

according to the residual moisture



HIGHLY POLISHED STEEL THIN CYLINDER

Rapid response to temperature, excellent thermal conductivity



		FCI2080/500	FCI2700/500	FCI3300/500
ROLLER DIAMETER	mm	502	502	502
USEFUL ROLLER LENGTH	mm	2080	2700	3320
HEATING				
Electric	kW	38	50	62
Gas	kW	42	56	69
Steam	kg/h	49	68	88
MOTORS				
Roller	kW	0.37	0.37	0.37
Fan	kW	0.55	0.55	0.55
TOTAL INSTALLED POWER				
Electric		39.3	51.2	62.9
Gas		1.2	1.2	1.2
Steam		1.1	1.1	1.1
EXHAUST	mm	1x150	1x150	1x150
IRONING CAPACITY*				
Electrical & Gas heating	kg/h	80	95	120
Steam heating	kg/h	95	115	145
IRONING SPEED	m/min.	1,5-10	1,5-10	1,5-10
ELECTRIC CONNECTION		380-415V 3AC+N 50/60 Hz 208-240V 3AC 50/60 Hz 380-415V 3AC 50/60 Hz 440V-480 3AC 60 Hz	380-415V 3AC+N 50/60 Hz 208-240V 3AC 50/60 Hz 380-415V 3AC 50/60 Hz 440V-480 3AC 60 Hz	380-415V 3AC+N 50/60 Hz 208-240V 3AC 50/60 Hz 380-415V 3AC 50/60 Hz 440V-480 3AC 60 Hz
DIMENSIONS				
H*W*D	mm	1410x2810x1100	1410x3430x1100	1410x4060x1100
Net weight (EL/G/S)	kg	1070/1030/1250	1220/1180/1400	1370/1330/1550
H*W*D (IR model)	mm	1410x2810x1261	1410x3430x1261	1410x4060x1261
TRANSPORT DATA				
Volume (crate packed)	m ³	5.54	6.75	7.96
H*W*D	mm	1558x2857x1244	1558x3481x1244	1558x4105x1244
Packed weight (EL/G/S)	kg	1250/1210/1430	1410/1380/1590	1580/1550/1760

